

SHIELDCOAT TECHNICAL DATA SHEET

CARAVAN COOL ROOF



DESCRIPTION

Thermobond Caravan Cool Roof is designed to transform your caravan, mobile home, or patio roof, offering a complete coating solution that goes beyond protection. This pack includes a specially formulated primer and membrane tailored to enhance both the appearance and temperature control of your roof. Covering an area of up to a 22ft caravan, it's the ideal choice for families looking to improve their mobile living experience.

Available in various colors

Gloss Finish, Semi-Gloss and Low Sheen.

SHIELDSEAL W PLUS - available in a 1L pail / THERMOBOND HRC - available in a 4L pail

APPLICATION GUIDE

- Stir the product thoroughly before use.
- Clean, dry, and repair any damage on the caravan roof.
- Apply the primer coat evenly using a roller or brush. Ensuring it has dried completely before moving on.
- Next, apply the membrane coat evenly using a roller or brush.
- For enhanced safety, wear gloves and goggles, and ensure proper ventilation.

 CARAVAN COOL ROOF MAXIMUM HEAT REDUCTION DRINKING WATER SAFE QUICK DRY	THERMOBOND HRC COVERAGE: 5-6 sqm/Lt TOUCH DRY: 60 Mins RECOAT: 4 Hours
	SHIELDSEAL W PLUS COVERAGE: 10-12 sqm/Lt TOUCH DRY: 20 Mins RECOAT: 2 Hours
	SHELF LIFE: 24 Months CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT