

SHIELDCOAT TECHNICAL DATA SHEET

GRAFFITISHIELD



DESCRIPTION

GraffitiShield is the ultimate solution for graffiti protection, making removal quick and easy. This non-sacrificial coating creates a protective barrier over walls, fences, buildings, or any surface in need of defense. Once applied, graffiti can be effortlessly wiped away with our graffiti remover and a rag. GraffitiShield is long-lasting, with multiple cleanings possible before reapplication is needed. Its water based formula is applied in two coats using a roller, brush, or airless spray gun, leaving a durable semi-gloss finish. Keep your surfaces protected with GraffitiShield today!

White liquid - Dries milky

Semi-Gloss.


Available in 15L pails



APPLICATION GUIDE

- High pressure wash with 2000+ psi to ensure the surface is free of any contaminants that may affect adhesion.
- If required, paint over any existing graffiti with 2 coats of a premium exterior acrylic paint. (Shieldcoat's Ultrashield)
- Allow 24hrs curing time before continuing.
- Apply 1 thin coat of GraffitiShield using a short nap roller, paint brush or airless sprayer using a 519 tip.
- Apply a

GRAFFITISHIELD



WATER
BASED



MOULD & DIRT
RESISTANT

COVERAGE: 12-14sqm/Lt

SOLIDS: 35 ave

WFT: 100um

DFT: 30um

TOUCH DRY: 2 Hours

RECOAT: 2-4 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT