

SHIELDCOAT TECHNICAL DATA SHEET

MOULDSHIELD C

DESCRIPTION

Mouldshield C is a powerful, concentrated cleaner designed to remove mould, fungi, grease, and oil from roofs, concrete driveways, walls, and industrial equipment. Safe for most surfaces when used as directed, it contains corrosion inhibitors to prevent damage. Commonly used to clean and prepare concrete before coating, it also removes bond breakers from tilt slab walls before painting. Care should be taken when cleaning soft metals like aluminium to avoid prolonged contact. Ideal for both residential and industrial cleaning applications.

Available in 15L pails



APPLICATION GUIDE

- Use Mouldshield C at the recommended concentration for the surface type.
- Apply the solution using a soft broom, backpack pressure sprayer, or brush to affected areas.
- Focus on removing mould, fungi, grease, oil, and bond breakers on concrete surfaces.
- Keep contact time short on soft metals like aluminium to prevent damage.
- For concrete preparation, allow time for etching and cleaning before coating.
- In some cases, a light rinse may be necessary to remove loosened contaminants.

MOULDSHIELD C

COVERAGE: Up to 200sqm

THINNING: 4:1 with water

RECOAT: Rinse off before
recoating

SHELF LIFE: 24 months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT