

SHIELDCOAT TECHNICAL DATA SHEET

NANOBOND ROOF MEMBRANE



DESCRIPTION

NanoBond is the latest innovation in roof coating technology, which achieves all the benefits of our already industry leading NanoProtect 4 coat system, with just 3 coats! As part of our continued investment in Research and Development, trials of a 3 coat system which could be offered with our unique "Colourfast" no fade warranty began in 2018. 6 years on, NanoBond was born.

45 standard colours, including all Colorbond colours. Gloss finish.

Semi-Gloss and Low Sheen also available.

Can be tinted from one of 6 coloured bases or via a tint pack into a clear base.

Available in 15L pails

APPLICATION GUIDE

- Nanobond is ready to use and does not require thinning.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 7°C or above 35°C.
- Nanobond is designed to be airless sprayed using a 521 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

NANOBOND ROOF MEMBRANE

6 YEARS

6 YEARS
NO FADE
WARRANTY



DRINKING
WATER
SAFE



MOULD & DIRT
RESISTANT

COVERAGE: 5-6sqm/Lt

SOLIDS: 50% ave

WFT: 180um

DFT: 90um

TOUCH DRY: 30 Mins

RECOAT: 2 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT