

SHIELDCOAT TECHNICAL DATA SHEET

SHIELDSEAL ULTIMATE

DESCRIPTION

Shieldseal Ultimate is a high build primer for porous concrete roof tiles. Formulated with a combination of high solids, high pigment loading and medium-high viscosity, Shieldseal Ultimate strikes the perfect balance between adhesion, coverage and usability. Shieldseal Ultimate is tinted to a light grey colour and available in 15Lt pails.

Grey liquid - Dries grey

Available in 15L pails

APPLICATION GUIDE

- Shieldseal Ultimate is ready to use and does not require thinning.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 7°C or above 35°C.
- Shieldseal Ultimate is designed to be airless sprayed using a 523 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

SHIELDSEAL ULTIMATE



MAXIMUM
COVERAGE



ADVANCED
ADHESION



MOULD
RESISTANT



DRINKING
WATER SAFE

COVERAGE: 5-6sqm/Lt

SOLIDS: 55% ave

WFT: 180um

DFT: 100um

TOUCH DRY: 30 Mins

RECOAT: 2 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT