

SHIELDCOAT TECHNICAL DATA SHEET

SHIELDSEAL W PLUS

DESCRIPTION

Shieldseal W Plus is an innovatively designed primer, engineered specifically for chalky Colorbond or other previously unpainted metal roofing materials. With its phenomenal adhesion capabilities achieved through a thin tack coat, this product sets a new standard in the primer industry. Coverage is exceptional, stretching up to 12 square meters per liter, providing unparalleled value. Formulated for quick application, Shieldseal W Plus makes the prep work fast and efficient, allowing you to move on to the finishing coats sooner.


Milky liquid - Dries clear

Available in 15L pails

APPLICATION GUIDE

- Shieldseal W Plus is ready to use and does not require thinning.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 7°C or above 35°C.
- Shieldseal W Plus is designed to be airless sprayed using a 517 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

SHIELDSEAL W PLUS



ADVANCED
ADHESION



QUICK
DRY



MOULD
RESISTANT



DRINKING
WATER SAFE

COVERAGE: 10-12sqm/Lt

SOLIDS: 20% ave

WFT: 90um

DFT: 20um

TOUCH DRY: 20 Mins

RECOAT: 2 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT