

SHIELDCOAT TECHNICAL DATA SHEET

SHIELDSEAL W

DESCRIPTION



Shieldseal W is a clear penetrating primer for non-porous concrete roof tiles and clay terracotta roof tiles. Shieldseal W dries quickly, is easy to apply and soaks into the substrate for maximum adhesion

Milky liquid - Dries clear

Available in 15L Pails

APPLICATION GUIDE

- Shieldseal W is ready to use and does not require thinning.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Avoid application when temperatures are below 7°C or above 35°C.
- Shieldseal W is designed to be airless sprayed using a 517 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

SHIELDSEAL W	COVERAGE: 7sqm/Lt SOLIDS: 22% ave WFT: 140um DFT: 30-35um TOUCH DRY: 20 Mins RECOAT: 2 Hours SHELF LIFE: 24 Months CLEAN UP: Water
 DRIES CLEAR  PENETRATES  MOULD RESISTANT  DRINKING WATER SAFE	

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT