

SHIELDCOAT TECHNICAL DATA SHEET

TERRABOND



DESCRIPTION

Terrabond is shieldcoat's ultra premium terracotta tile sealer. This high-gloss, 100% acrylic clear coating seals and protects your terracotta surfaces. Its water - based formula is easy to apply, quick to dry, and allows for same-day re-coats. UV resistant and weather resilient, Terrabond keeps your surfaces in pristine condition, reflecting Shieldcoat's commitment to quality and durability.

Clear liquid - Dries clear

Available in 15L pails



APPLICATION GUIDE

- Terrabond is ready to use, with no thinning required, however if desired thin with water sparingly.
- If mould is present, apply 1 coat of Mouldshield C.
- Pressure clean the roof with 3000+ psi, taking care to thoroughly rinse the roof at the end.
- Apply 2 thin coats of Terrabond.
- Avoid application when temperatures are below 7°C or above 35°C.
- Terrabond is designed to be airless sprayed using a 519-521 or similar spray tip.
- Allow extra curing time in winter months and do not spray after 2pm where possible.

TERRABOND			COVERAGE: 5-6sqm/Lt WFT: 100um DFT: 25um TOUCH DRY: 20 Mins TOPCOAT: 12 Hours CLEAN UP: Water
A shield icon with a water drop inside, labeled 'DRINKING WATER SAFE'.	A chain link icon, labeled 'EXCELLENT ADHESION'.	A water drop icon, labeled 'WATER BASED'.	

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT