

SHIELDCOAT TECHNICAL DATA SHEET

ULTRANAMEL DOOR & TRIM



DESCRIPTION

UltraNamel Door & Trim utilises advanced pure acrylic and polyurethane resin technology to produce an exceptionally durable trim paint. It dries rapidly, has a low odour, and can be easily cleaned up with water.

Designed mainly for airless spray application, UltraNamel Door & Trim provides a smooth, flat finish that is simple to achieve. For those who favour using a brush, they will enjoy the distinctive, silky, low-drag texture that Shieldcoat products are renowned for.



WHITE BASE AND FACTORY TINTED

1, 5, and 10 L




Semi-Gloss, Low Sheen



APPLICATION GUIDE

- Stir the product thoroughly before use.
- Make sure the substrate is clean and free from any contamination, such as dirt, dust, or oils.
- Avoid application when temperatures are below 7°C or above 35°C.
- UltraNamel Door & Trim can be applied using a brush, roller, or airless spray gun.

ULTRANAMEL DOOR & TRIM



COVERAGE: Up to 12sqm/Lt

SOLIDS: 50% ave.

WFT: 80um

DFT: 40um

TOUCH DRY: 30mins

RECOAT: 2 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT