

SHIELDCOAT TECHNICAL DATA SHEET

WATERSHIELD A WATERPROOFING MEMBRANE

DESCRIPTION

Watershield A by Shieldcoat is an advanced waterproofing membrane designed to provide superior protection against water damage for various surfaces, including concrete, wood, metal, and masonry. Engineered for both residential and industrial applications, it creates a durable barrier against leaks, erosion, and decay, ensuring long-lasting defense. With exceptional adhesion and resistance to moisture, Watershield A reflects Shieldcoat's commitment to quality and reliability, offering peace of mind and long-term protection.

Available in a Low Sheen finish.


15L pails

RECOMMENDED USE: It is suitable for use over concrete, asbestos, bitumen and metal deck roofs, concrete and brick wall cladding, plasterboard, storage tanks, structural steel, behind masonry retaining walls and box gutter repairs. It is excellent for waterproofing walls, floors and shower cubicles in bathrooms and before laying tiles. Watershield A can be used in conjunction with a poly cloth to create an even stronger barrier against water.


APPLICATION GUIDE

- Stir the product thoroughly before use, thinning is not required.
- Ensure surfaces are clean, dry, and suitable weather conditions exist.
- For concrete, cure for 28 days and maintain moisture below 6%. For metal, repair rust and replace rusty screws.
- Ensure metal areas are thoroughly primed with RUSTSHIELD W. Prime all other areas listed above with SHIELDSEAL W PLUS as directed.
- Apply three coats of WATERSHIELD A. (CAN BE SPRAYED OR ROLLED)


WATERSHIELD A WATERPROOFING MEMBRANE



LONG LASTING
PROTECTION



ADVANCED
ADHESION



WATER
BASED

COVERAGE: 2.5sqm/Lt

SOLIDS: 62% ave

WFT: 400um

DFT: 248um

TOUCH DRY: 1 Hour

RECOAT: 4 Hours

SHELF LIFE: 24 Months

CLEAN UP: Water

DISCLAIMER: Shieldcoat emphasizes that it is the responsibility of the applicator to assess and confirm the product's suitability for its intended use before application. The information and recommendations provided in this document were accurate and valid at the time of writing.



SHIELDCOAT