



TECHNICAL DATA SHEET

ULTRASHIELD CEILING WHITE

DESCRIPTION: SHIELDCOAT ULTRASHIELD CEILING WHITE is a water-based premium quality, acrylic, flat paint for use on interior ceilings.

RECOMMENDED USE: As a high quality acrylic ceiling white suitable for interior paper faced plasterboard, and fibro ceilings.

APPLICATION PROCESS: Shieldcoat recommended surface preparation is crucial and is the responsibility of the Builder/Contractor/Applicator. Weather conditions must be considered and deemed suitable before proceeding. High humidity will affect drying and recoat times.

When renovating fibro surfaces which could contain asbestos, please download and read the ASBESTOS RENOVATION GUIDE available on the following link.

<http://www.deir.qld.gov.au/asbestos/resources/pdfs/asbestos-home-renovators-trades-guide.pdf>

General Preparation

Scrape off all loose or flaking paint. Fill cracks, nail holes and imperfections with a suitable water based filler and sand smooth. Fill gaps in cornice and architraves with a suitable gap filler

Previously Painted Surfaces

Wash entire surface using a sugar soap solution as per instructions, rinse thoroughly with fresh water, replace rinse water regularly, allow to dry thoroughly before proceeding to general preparation above.

Plasterboard,

Surface must be clean dry and dust free. Apply one coat of ULTRASHIELD SEALER UNDERCOAT. Sand the entire surface to a smooth finish.

Masonry, Render, Brick, Concrete, Fibro

Remove all contaminants by washing down with a sugar soap solution as per instructions. Apply one coat of ULTRASHIELD 3in1 UNDERCOAT.

Thinning & Clean Up

Thinning is not recommended. Clean equipment with water immediately after use.



TECHNICAL DATA SHEET

ULTRASHIELD CEILING WHITE

DESCRIPTION: SHIELDCOAT ULTRASHIELD CEILING WHITE is a water-based premium quality, acrylic, flat paint for use on interior ceilings.

RECOMMENDED USE: As a high quality acrylic ceiling white suitable for interior paper faced plasterboard, and fibro ceilings.

APPLICATION PROCESS: Shieldcoat recommended surface preparation is crucial and is the responsibility of the Builder/Contractor/Applicator. Weather conditions must be considered and deemed suitable before proceeding. High humidity will affect drying and recoat times.

When renovating fibro surfaces which could contain asbestos, please download and read the ASBESTOS RENOVATION GUIDE available on the following link.

<http://www.deir.qld.gov.au/asbestos/resources/pdfs/asbesv-tos-home-renovators-trades-guide.pdf>

General Preparation

Scrape off all loose or flaking paint. Fill cracks, nail holes and imperfections with a suitable water based filler and sand smooth. Fill gaps in cornice and architraves with a suitable gap filler

Previously Painted Surfaces

Wash entire surface using a sugar soap solution as per instructions, rinse thoroughly with fresh water, replace rinse water regularly, allow to dry thoroughly before proceeding to general preparation above.

Plasterboard,

Surface must be clean dry and dust free. Apply one coat of ULTRASHIELD SEALER UNDERCOAT. Sand the entire surface to a smooth finish.

Masonry, Render, Brick, Concrete, Fibro

Remove all contaminants by washing down with a sugar soap solution as per instructions. Apply one coat of ULTRASHIELD 3in1 UNDERCOAT.

Thinning & Clean Up

Thinning is not recommended. Clean equipment with water immediately after use.



TECHNICAL DATA SHEET

ULTRASHIELD CEILING WHITE

RECOMMENDATIONS AND PRECAUTIONS

Ensure that appropriate workplace health and safety methods and PPE are used when working with this product.

Ensure adequate ventilation when using this product.

Care and Maintenance: Protect the coating from abrasive contact for 10 days. Wash down periodically with a mild detergent solution to refresh and preserve the coating.

MSDS: Available on request or download from the Shieldcoat website. www.shieldcoat.com.au

DISCLAIMER: Shieldcoat advises that the applicator of this product is responsible to determine and verify its suitability for the intended use prior to application. The data and recommendations contained within this document were true and accurate at the time of writing.